

SPX-750-S/U SERIES

750 WATT (-S) SELECTABLE OR (-U) UNIVERSAL INPUT
ONE TO FOUR OUTPUTS



HIGH RELIABILITY GREATER THAN 120,000 HRS. MTBF



FEATURES:

100 KHz Operation
Sizes 5" x 2.6" x 13.5"
75% Efficiency Typical
Meets EN55022 Level A / FCC Class A

TYPICAL MODELS AND THEIR OUTPUT RATINGS:

MODEL NO.	V1	V2	V3	V4
SPX-750T-SF	5/100A	12@12/20Apk	-12/10A	
SPX-750Q-UF	5/120A	15@6/10Apk	-5.2/6A	12/2A
SPX-750Q-UF	5/120A	12@12/20Apk	-12/10A	5.2/2A
SPX-750Q-SF	5/120A	24@6/10Apk	-12/10A	15/2A

or configure your own output requirements from the chart below:

	OUTPUT VOLTAGE (VDC)	OUTPUT AMPERS (MAX)	OUTPUT POWER (WATTS)
V1	2 to 48	120	750
V2	2 to 48	12	180
V3	2 to 48	10	120
V4	5 to 48	2	50



3601 VETERANS HIGHWAY
RONKONKOMA, NEW YORK 11779
TEL (631) 981-7231 FAX (631) 981-7266

VISIT US ON THE WEB:
<http://www.switchpwr.com>

